

TECHNICAL DATA SHEET

AF 100 100% active silicone defoamer

Description

CHT USA's 100% active defoamers are formulated to control foam in a wide variety of industrial processes.

Key Features

- Excellent foam knockdown and persistence
- Effective in low concentrations
- Effective in hot and cold systems
- Easy to handle

Key Applications

- Coatings
- Food starch and protein washes
- Pulp and paper
- Waste water treatment

Application

AF 100 is used in to control foam in industrial applications including coatings, oil and gas, food starch and protein washes, beverages, pulp and paper and waste water treatment.

Use and Cure Information

100% active silicone defoamers can be dispersed with minimal agitation in most nonaqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system, or dilute with process liquid prior to use. Effective when added prior to foam generation or when added to control existing foam.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations:

This product is not intended for pharmaceutical use.

Property

Product

% actives
Appearance
Color
Viscosity (cst)

Addition Rates

Dosage - 1

Dosage - 2

Storage

Max Storage Temperature

Packaging

Shelf Life

Test
Method Value

100 %
Liquid
Greyish white
3000

As defined by FDA regulation
21 CFR 173.340, defoaming
agents used in processing
foods.

100-10,000ppm active in
industrial applications.

40 °C / 104 °F

This product is available for
sale as 40 lb. pails and 441 lb.
drums. and 2205 lb. totes
12 mths

Revision Date 21 Sep 2021
Revision No 6
Download Date 19 May 2024