TECHNICAL DATA SHEET



4 °C / 39 °F

drums

12 mths

32 lb. pails or 325 lb.

EM 1642 High-end nonionic emulsion of silicone crosspolymer

Description	Property	rest	Value
This product is a emulsion of a crosspolymer gel.	-13	Method	
Key Features	Product		
Excellent surface leather conditioner	Appearance		Milk White
 Improves touch and surface slip 	Ionicity		Non-ionic
 Provides a light scattering matte effect 	MIT Free		Yes
Key Applications	Solids Content (%)		8 %
• Leather	Ultralow cyclic content		No
Automotive surfacesSynthetic surfaces	Viscosity (cst)		100000
• Tires Application	Addition Rates Dosage - 1		0.5-25
ICM EM 1642 is a emulsion of a crosspolymer gel that is designed for use on leather and other interior automotive	Storage		0.0 =0
surfaces to reduce glare and improve touch properties. ICM EM 1642 can also be used as a high end, long lasting slip aid for	Max Storage Temperature		40 °C / 104 °F
1072 can also be used as a riight end, long lasting slip aid lon	M's Observed Towns and the		4.00 / 00 05

sliding windows and doors as well as an anti-squeak additive for automotive interiors.

Use and Cure Information

This product is compatiable with aqueous systems and can be added directly to the formulation with minor agitation.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Min Storage Temperature

Packaging

Shelf Life

Limitations

This product is not intended for pharmaceutical use.

Revision Date 21 Sep 2021

Revision No 6

Download Date 19 May 2024