## TECHNICAL DATA SHEET



## HANSA CARE 7140 ECO Silicone solution as an ingredient for Home and Car Care.

Description

Aminosiloxanes are Siloxanes modifed with Nitrogen groups. The modification degree lead to an

optimal performance in aqueous or solvent borne formulations for home and car care applications.

These products are excellently suited for a use in polishes, wax formulations and drying aids in automatic or manual car wash and provide for perfect drying characteristics including a good water repellence and excellent gloss.

**Key Features** 

Water repellency

Durability

Color depth and Color restoring properties

Softness and smoothness

**Key Applications** 

Impregnation for fabrics / textil

Leather. Furniture and Fabric Care

Stone and wood impregnation

Car Care Treatments

**Application** 

HANSA CARE 7140 ECO is particularly suited for formulating wash-in impregnations for textiles in the washing machine. Due to its chemical structure a very good water repellency is achieved on all synthetic textiles. The complete impregnation effect is already achieved by drying at room temperature. Moreover, it is also suited for impregnating glass, varnishes, leather, wood, mineral grounds, etc. Varnish and glass sealings for automotive, aircrafts and boat care based on HANSA CARE 7140 ECO are particularly well stable and facilitate an easy removal of soilings.

**Health & Safety** 

**Health & Safety** 

Safety Data Sheet available on request.

**Packaging** 

Drums and bulk containers. Please contact our sales department for more information.

Revision Date 09 Mar 2023

Revision No

**Download Date** 19 May 2024

Method Value **Property** 

Product

Appearance Clear to slightly turbid liquid

> Aqueous solution of a reactive aminomodified

Chemistry polysiloxane

BS ISO Density Approx. 1.0 g/cm3 2781

Ionicity Cationic MIT Free Yes Non-Volatile Content (%) Approx. 15 Ultralow cyclic content Yes pH (10% solution) 4-5

**Addition Rates** 

20.0 - 30.0% in wash-in Dosage - 1 impregnation for textile 1.0 - 10.0% in impregnations Dosage - 2

for textile or other surfaces 1.0 - 10.0% in car polishes / Dosage - 3

sealants

Storage

40 °C / 104 °F Max Storage Temperature Min Storage Temperature 4 °C / 39 °F Shelf Life 6 mths

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.