## **TECHNICAL DATA SHEET**



## AF 100 100% active silicone defoamer

**Property** 

Product

% actives

Description

CHT USA's 100% active defoamers are formulated to control foam in a wide variety of industrial processes.

**Key Features** 

• Excellent foam knockdown and persistence

Effective in low concentrations

· Effective in hot and cold systems

• Easy to handle

**Key Applications** 

Coatings

Food starch and protein washes

· Pulp and paper

Waste water treatment

**Application** 

AF 100 is used in to control foam in industrial applications including coatings, oil and gas, food starch and protien washes, beverages, pulp and paper and waste water treatment.

**Use and Cure Information** 

100% active silicone defoamers can be dispersed with minimal agitation in most nonaqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system, or dilute with process liquid prior to use. Effective when added prior to foam generation or when added to control existing foam.

Appearance Color Viscosity (cst)

Addition Rates

Dosage - 1

Dosage - 2

----

Storage

Max Storage Temperature

Packaging

Shelf Life

As defined by FDA regulation

21 CFR 173.340, defoaming agents used in processing

foods.

100 %

Liquid

3000

Greyish white

Method Value

100-10,000ppm active in

industrial applications.

40 °C / 104 °F

This product is available for sale as 40 lb. pails and 441 lb.

drums. and 2205 lb. totes

12 mths

**Health & Safety** 

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

## Limitations

This product is not intended for pharmaceutical use.

Revision Date 21 Sep 2021

Revision No

Download Date 27 Apr 2024