TECHNICAL DATA SHEET



White liquid

EM 1407 40% Active Emulsion of a High Molecular Weight Polydimethylsiloxane

Appearance

Description
This product is an industrial anionic polydimethylsiloxane

Property
Test
Method Value

emulsion Product

Long lasting lonicity Anionic

Effective in low concentrations Solids Content (%)

Excellent wetting/spreading on surfaces

Easily dispersed in water with minimal agitation

Anionic

42 %

8.0

Key Applications Addition Rates

Release agent
 Auto care
 Dosage - 1
 0.1 - 1%

Leather conditioning
 Rubber treatment
 Application
 Storage
 Max Storage Temperature
 40 °C / 104 °F

EM-1407 is a 40% active emulsion of a high molecular weight silicone polymer. The high molecular weight dimethicone actives

Packaging

Packaging

Packaging

Packaging

Packaging

10 path 2

are delivered in an opaque, low viscosity liquid with neutral pH.

This emulsion was developed as an effective release agent at

low concentrations. EM 1407 is a superior release agent, but has exceled in a wide variety of applications including, hydrophobic coatings, leather conditioning, and automotive care.

Use and Cure Information

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring.

Health & Safety

Key Features

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

Revision Date 03 Jan 2024

Revision No 11

Download Date 05 May 2024