

## EM 2750I 60% Active Emulsion of Organic Polymers and Polydimethylsiloxane

### Description

This product is an industrial nonionic polydimethylsiloxane emulsion.

### Key Features

- Chemically inert - will not gum up heat set printing mills
- Smooth topcoat hides printing imperfections and improves slip
- Can be combined with additional antistat agents in dry environments without sacrificing emulsion stability
- High solids formulation allows for end use dilution as desired

### Key Applications

- Printing applications
- Heat set printing mills
- Polish formulations
- Printing and foundry release

### Application

EM 2750I is a 60% active emulsion of a complex blend of organic polymers and dimethyl polysiloxane fluids. This product is easily diluted with water, demonstrates excellent dilution stability at very low concentrations and is chemically inert. EM 2750I may be formulated with either a cationic or an anionic system since it is made with nonionic emulsifiers. It can also be formulated with an antistat upon customer request. This emulsion has been specially formulated for roll-to-roll high speed printing. The active polymers seal the ink into the paper, provide improved shine and eliminates the appearance of printing flaws.

### Use and Cure Information

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring.

### Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

### Limitations

This product is not intended for pharmaceutical use.

### Property

#### Product

Appearance  
Ionicity  
Solids Content (%)  
pH

#### Storage

Max Storage Temperature  
Packaging  
Shelf Life

### Test Method

### Value

White liquid  
Non-ionic  
60 %  
7.5  
40 °C / 104 °F  
40 lb. pails, 441 lb. drums,  
and 2205 lb. totes  
12 mths

Revision Date      12 Feb 2024  
Revision No        6  
Download Date     05 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

**CHT Germany GmbH:** Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany  
Telephone: 07071/154-0, Fax: 07071/154-290, Email: [info@cht.com](mailto:info@cht.com), Homepage: [www.cht.com](http://www.cht.com) / [www.cht-silicones.com](http://www.cht-silicones.com)