TECHNICAL DATA SHEET



ICM EM 1642 High-end nonionic emulsion of silicone crosspolymer

Test

Value

Description **Property** Method This product is a emulsion of a crosspolymer gel. **Product Key Features**

Milk White Excellent surface leather conditioner Appearance Improves touch and surface slip Ionicity Non-ionic Provides a light scattering matte effect MIT Free Yes **Key Applications** Non-Volatile Content (%) 8

Leather Ultralow cyclic content No Tires Viscosity (cst) 100,000 Synthetic surfaces

Addition Rates Application Dosage - 1 0.5-25.0%

ICM EM 1642 is a emulsion of a crosspolymer gel that is designed for use on leather and other interior automotive Storage surfaces to reduce glare and improve touch properties. ICM EM Max Storage Temperature 40 °C / 104 °F 1642 can also be used as a high end, long lasting slip aid for Min Storage Temperature 4 °C / 39 °F sliding windows and doors as well as an anti-squeak additive for automotive interiors. 32 lb. pails or 325 lb.

Packaging **Use and Cure Information** drums Shelf Life 12 mths This product is compatiable with aqueous systems and can be

Health & Safety Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

added directly to the formulation with minor agitation.

Revision Date 21 Sep 2021

Revision No

Automotive surfaces

Download Date 02 May 2024